

T23 – Sheathed thermocouple, compacted MgO insulation with connector directly on the sheath and fixed mounting fitting.



Sample shown: T23-MU-3K-CI-18PP

T23- $\frac{\quad}{1}$ $\frac{\quad}{2}$ - $\frac{\quad}{3}$ $\frac{\quad}{4}$ - $\frac{\quad}{5}$ $\frac{\quad}{6}$ - $\frac{\quad}{9}$

- 1 – Connector:** S – Molded on standard plug
J – Standard jack
M – Molded on mini plug
MJ – Mini jack
- 2 – Junction Type:** G – Grounded
U – Ungrounded
U2 – Ungrounded Separate for Dual Element
E – Exposed
S – Semi-shielded

3 – Probe length: In inches
As measured from the tip to the first fixed attachment.



206 Industrial Parkway Drive • Boyne City, Michigan 49712 • (800) 582-5098 • Fax (231) 582-9491
www.temprel.com

4 – Calibration: E K J T

5 – Sheath diameter:

| | |
|-------------|-----------|
| AAA - .032" | C - .125" |
| AA - .040" | D - .188" |
| A - .062" | E - .250" |
| B - .090" | |

6 – Sheath material:

- H - Hastelloy X®
- I – Inconel®
- S – 304 SS
- S10 – 310 SS
- S16 – 316 SS

9 - Options: Specify mounting fitting or part number of oil drain plug.